

# Cleanroom Mop

Polyester mop for floors, walls and ceilings



22-29  
TruCLEAN Cleanroom Mop

## Applications

- Recommended for ISO class 3 cleanroom environments
- Designed for cleaning floors, walls and ceilings
- For use with all TruCLEAN Mopping Systems
- Perfex Cleanroom Mop designed for use with TruCLEAN Stainless-Steel Mop Frame

## Description

TruCLEAN Cleanroom Mop is constructed of continuously woven polyester fabric, individually packaged and laundered in a class 100 cleanroom facility. Tubular knit loops conform to almost any shape, making cleaning of baseboards and wall joints easier. Dampen prior to autoclaving, up to 250° F (121° C) for 30 minutes. Also launderable in a standard washing machine.

## Features

- Mop-to-dry performance on wet surfaces
- Compatible with Gamma, ETO and autoclave sterilization
- 16"(40cm) x 5"(12.7cm) coverage area with a single pass
- Quick changing mop head configuration

## Benefits

- Can be repeatedly laundered and autoclaved providing exceptional value.
- Looped-end construction provides excellent durability
- Impervious to a wide range of chemicals

## Product Information

Part #	Description	Material
22-29	TruCLEAN Cleanroom Mop	Polyester
<b><i>Accessories:</i></b>		
22-38	TruCLEAN Mop Frame	Type 304 Stainless Steel
22-57	TruCLEAN Adjustable Handle	Polymer

## Ordering Information

Part #	Description	Carton Size (L x W x H)	Carton Weight	Packaging
22-29	TruCLEAN Cleanroom Mop	19" x 5" x 3"	1 lbs.	1/each
		18" x 7" x 6"	5 lbs.	12/case