

VINYL GLOVE

POWDERED & POWDER-FREE



Functional Benefits

- Intrinsic softness reduces hand fatigue even for long hours of wearing these gloves, due to low 100% modulus 25 kg/cm^2 comparing with normal commercial product at 3 kg/cm^2 ; super flexibility and light weight.
- Double layers of PVC/PU films to provide double protection.
- Odor free, results from special formulations.
- Ease in donning due to the excellent slippery inner surface.
- In grip from slightly tacky outer surface.



vinyl glove

VINYL GLOVE

POWDERED & POWDER-FREE

Quality Standards

- Conforms to ASTM D5250 and EN455 Standards

Glove Sizes

- Extra Small, Small, Medium, Large, Extra-Large
- Marked in the check box on the shipping carton with black ink

Product Specifications

Type	Powdered or Powder-free and non-sterile
Material	Polyvinyl Chloride paste resin, Grade: FPC DNV2P
Design & Features	Ambidextrous, beaded cuff; clear or coloured (blue)
Storage	The gloves shall maintain their properties when stored in a dry condition at temperature between 10 to 30°C. Protect gloves against ultra violet light sources, such as sunlight and oxidizing agents. Copper ions discolor the glove.
Shelf-life	5 years from date of manufacturing

Physical Dimensions

DIMENSIONS	STANDARDS	
	Glove	ASTM D5250-06
Length (mm) Minimum	230 min	230 mm for all sizes
Width (mm)		
• Extra-small	75 ± 5	
• Small	85 ± 5	85 ± 5
• Medium	95 ± 5	95 ± 5
• Large	105 ± 5	105 ± 5
• Extra-large	115 ± 5	115 ± 5
Thickness - Single Wall (mm)		
• Fingers	0.05 min	0.05 min
• Palm	0.08 min	0.08 min

Physical Properties

Property	ASTM D5250
Elongation at break (%)	Min 300
Tensile Strength (MPa)	Min 11



International Quality System Certificate Awarded



GERMANY



U.S.A



AUSTRALIA



Standard Malaysian Glove
Certificate Approval No. 2004



CANADA



QUALITY SYSTEM
MALAYSIA