

| Technical Support

Item	Standard	Data		
Electrical Resistance(Ω)	SJ/T11236-2001	Conductive EC	Dispassive SD	Test Result
		2.5*10 ⁴ - 1.0*10 ⁶	1.0*10 ⁶ -10 ⁹	
Dimensional(%)	ISO 23999:2018	0.05		Test Report
Stating Voltage	SJ/T11236-2001	50V	100V	/
Static Decay(s)	GJB2605-1996	≤ 2		/
Wear Resistance	EN 660-2:1999	Class P		Test Report
Fire Resistance	EN13501-1:2007	Bfl-s1		Test Report
Radiant Flux(W/cm ²)	ASTM E648-2017	≥ 1.1		Test Report

Slip Resistance Wet	EN13893	≥ 0.3	/
Residual Indentation(mm)	ISO 24343-1:2002	0.01	Test Report
Color Fastness	ISO 105B 02	≥ 6	Test Report
Chemical Products Resistance	EN ISO 26987:2012	OK	Test Report
Migration of Certain Elements	EN 71-3:2013	OK	Test Report
RoHS Directive(%)	EN 62321	0.003	Test Report
TVOC After 28 Days($\mu\text{g}/\text{m}^3$)	ISO 16000-3	<10	Test Report